

PROCESS AND DEVICE FOR CALCULATING THE POSITION OF A
MOBILE STATION, CORRESPONDING COMPUTER PROGRAM AND
MEMORY MEDIUM

The domain of this invention is radiocommunication systems for communication with mobiles, particularly but not exclusively according to the UMTS (Universal Mobile Telecommunication System - 2 GHz), GSM 900 (Global System for Mobile - 900 MHz), DCS 1800 (Digital Cellular System - 1800 MHz) and PCS 1900 (Personal Communication System - 1900 MHz) standards.

More precisely, this invention relates to a process and a device for calculating the position of a mobile station belonging to a cellular radiocommunication system starting from an identifier of a current geographic cell in which this mobile station is located.

A "current geographic cell" means the cell in which the mobile station is located at the given moment. Remember that mobile stations move within a network of geographic cells. Each cell is associated with a base station that allows mobile stations within this cell to send and receive calls.

The terms "mobile station", "radiotelephone" and "mobile" are used indifferently in the remainder of this description.

Conventionally, mobile positioning information is associated with signalling information related particularly to the identities of these mobiles, to enable the supply of geodependent services (in other words services related to positioning of mobiles). For example, geodependent services are intended to manage a fleet of vehicles or to provide information depending on the position (for example the local weather, downloading of geographic maps, indication of the closest restaurant, hotel, garage, etc.), possibly with routing of the call accordingly (by modifying the requested number).

Typically, the associated positioning and identification information for the different mobile stations is input to a positioning database that is referred to by geodependent service providers to satisfy requests from their customers. Typically, this positioning database is stored on a positioning server.

In the rest of this description, it is assumed that "raw" positioning information is available in the form of an identifier (for example the BSCI according to the GSM terminology) for the current cell in which the mobile is located. Typically, this is equivalent to considering that positioning is done by the network subsystem (NSS according to the GSM terminology) that determines the current cell starting from cell information contained in a signalling message (or a short message) sent by the mobile.

Consequently, we will not discuss other "radio frequency positioning" techniques such as GPS (Global Positioning System), OTD (Observed Time Distance), E-OTD (Enhanced Observed Time Difference), TDOA (Time Difference of Arrival), TA (Timing Advance), AOA (Angle of Arrival), etc. in this description.

The current technique for using the cell identifier as positioning information consists of using only the

Preferably, the said calculation of a modelled
5 geographic representation of the current cell consists
of using a radio prediction tool to calculate a set of
points in which the radio frequency field in the current
cell is stronger than that in other cells.

Preferably, the said geometric shape belongs to the group comprising disks and polygons (preferably hexagons, squares and equilateral triangles). These geometric shapes help to simplify the calculations. However, it is clear that other geometric shapes could be envisaged without going outside the scope of this invention.

30 In one particular embodiment of the invention, the position of the mobile station is calculated dynamically. In this way, this invention makes it easy to adapt to any change in the geographic cells network.

Advantageously, the said process comprises a prior
35 step to extract the identifier of the current cell from

at least one signal message circulating on the radiocommunication system network.

In one particular embodiment, the said extraction is triggered if at least one of the following conditions is satisfied when the mobile station makes a call:

- the number of the mobile station belongs to a predetermined list of calling numbers;
- the number called by the mobile station belongs to a predetermined list of called numbers;
- the current cell belongs to a predetermined list of cells.

According to one advantageous application, the position of the mobile station and the associated uncertainty are input into a positioning database to enable the supply of at least one geodependent service.

This positioning database can be queried by a single geodependent service provider, or it may be shared by several geodependent service providers. For example, it may be managed by the radiocommunication system operator.

For each mobile with a defined position, the positioning database stores:

- a mobile identifier (for example IMSI or TMSI);
- the position of the mobile with the uncertainty on this position, resulting from the barycentre calculation according to the invention;
- any other signalling information, for example related to the requested communication type, the requested number, etc.

The invention also relates to a device for calculating the position of a mobile station belonging to a cellular radiocommunication system starting from the identifier of a current geographic cell in which the said mobile station is located. The device according to the invention comprises:

- means of calculating a modelled geographic representation of the current cell;

- means of calculating the barycentre of the said modelled geographic representation of the current cell;

- means of calculating an uncertainty area, with a predetermined geometric shape centred on the said barycentre and the area of which is approximately equal to the area of the said modelled geographic representation of the current cell;

the position of the mobile station being defined by the said barycentre with an uncertainty equal to the said uncertainty area.

Preferably, the said device is integrated into a radio frequency planning tool for the geographic cells in the said cellular radiocommunication system.

In this way, the costs are limited by using equipment already available to the operator.

The invention also relates to a computer program comprising instruction sequences adapted to the use of a process for calculating the position of a mobile station according to the invention.

The invention also relates to a memory medium that can be read by a computer and that contains a program that, when it is executed by the computer, makes the computer capable of using the process to calculate the position of the mobile station according to the invention.

Other characteristics and advantages of the invention will become clear after reading the following description of a preferred embodiment of the invention, given as an example for information and which is in no way limitative, and the attached drawings in which:

- FIGURE 1 contains a block diagram illustrating a radiocommunication system in which a particular

- FIGURES 2 to 5 each illustrate a particular embodiment of the geometric shape (disk, square, hexagon and triangle respectively) of the uncertainty area calculated by the process according to the invention;

- FIGURE 7 shows a block diagram of a particular embodiment of the process for calculating the position according to this invention, shown in FIGURE 1.

A cellular radiocommunication system according to the GSM standard is considered in the remainder of the description. However, it is obvious that the invention is not limited to this type of system.

Remember that conventionally, a cellular GSM network comprises at least one mobile service switch (MSC according to the GSM terminology) enabling interconnection of the cellular network with a fixed telephone network (for example the Public Switched Telephone Network). At least one base station controller (BSC, according to the GSM terminology) is connected to each MSC. At least one base station (BTS according to the GSM terminology) is connected to each BSC. Each BTS provides coverage for a distinct geographic area called a "cell" in which mobile stations (MS according to the GSM terminology) can move around. Part of such a GSM network is illustrated in FIGURE 1, which diagrammatically shows an MSC, a BSC, three base stations BTS_1 to BTS_3 and a mobile MS. At the moment

considered, it is assumed that the current cell of the mobile MS is the cell associated with the base station reference BTS₁.

In a particular embodiment illustrated by the simplified flow chart in FIGURE 6, the process according to the invention comprises the following steps:

- extract (61) the current cell identifier contained in a signalling message;
 - calculate (62) the modelled geographic representation of the current cell;
 - calculate (63) the barycentre of the modelled geographic representation, this barycentre being the calculated position of the mobile;
 - calculate (64) an uncertainty area, defining the uncertainty on the calculated position of the mobile;
 - input data (65) to a positioning database, with the position of the mobile station and the associated uncertainty.
- We will now describe each of these steps 61 to 65 in detail.

Step 61: extract the current cell identifier contained in a signalling message.

When the mobile starts a call in telephony mode (circuit outgoing call) or in packet mode (GPRS, UMTS or SMS outgoing call), the signal circulating on the network subsystem (NSS) carries the calling party's number, the called party's number and the identifier of the cell from which the call originated (current cell). This information is present particularly in the initial address message (MIF/IAM in CCITT No.7 signalling) that passes through the MSC.

As shown in FIGURE 1 as an example, the following capture and extraction mechanism may be used according to the intelligent network (IN) concept, in order to obtain this information:

5 to the Service Check Point (SCP);

10 calculation device 1.

15 (GPRS, UMTS or SMS outgoing call) without going outside
the scope of this invention.

20 mentioned:

- the calling number belongs to a predetermined list of calling numbers.

```

25  service;

```

- the called number belongs to a predetermined list of called numbers. For example, calls to particular servers may be detected. For example, they may be servers of geodependent service providers 3₁, 3₂;

30 - the current cell belongs to a predetermined list of cells.

Step 62: calculate the modelled geographic representation of the current cell.

35 current cell is calculated using a radio prediction tool
to calculate a set of geographic points in which the

current cell has a radio frequency field stronger than in other cells ("best server" concept). In other words, the mobile locks on to this cell (in other words it communicates through the base station associated with this cell) only at these geographic points. Elsewhere, the mobile switches to other cells by handover or reselection.

For example, the layout of the area of a geographic cell may be calculated dynamically by an RF (radio frequency) planning tool that the operator already has for management and maintenance of his network. This tool is also sometimes called a "cellular network radio prediction tool".

The radio prediction tool is software that starts from base station data and calculates the electrical field produced at all geographic points. The base station is characterized in this respect by the antenna diagram (X, Y, Z) describing the gain in dB applicable to each direction starting from the base station, and by the power supplying the antenna at the RF frequency considered.

The calculation algorithms used are broken down into two families:

- "heuristic" methods: the electrical field is obtained by a logarithmic addition (in dB) of the various attenuations of the path considering the relief and the nature of the ground along the path. The most common is the Okumura-Hata formula;

- "start beam" or similar methods: the algorithm attempts to reconstruct radio electric wave paths to deduce the attenuation along the path (for example Walfish-Ikegomi).

These calculations give approximate values (errors of the order of 6 dB tolerated).

The "pixel" (basic element) used in the calculation is a square, for example 50 m x 50 m. The calculation

090604Z-092001
10320-549999

When the value of the field received from the various base stations is available at a given point, the "best server" calculation consists of comparing these data and identifying the cell that produces the highest electrical field.

10

- 15

Step 63 - calculate the barycentre of the modelled geographic representation.

20

Step 64 - Calculate the uncertainty area

25

35

barycentre of this geographic representation reference 6, and the uncertainty area reference 7.

In general, if the geometric shape is a polygon, the polygon is oriented along the larger direction of the current cell. For example, the orientation process may consist of scanning the area of the modelled geographic representation ("best server" area) using a straight line passing through the barycentre and being equal to all possible orientations in sequence (for example, North to East, then South, West, and then North again). The segments intercepted between the barycentre and the most remote point are then measured. Finally, the "vertex" (or one of the "vertices") of the polygon is oriented in the direction in which the largest intercepted segment was measured. In other words, the largest intercepted segment is aligned with the diagonal of the square, or with the height of the equilateral triangle, or with the "diameter" of the hexagon.

This invention is particularly advantageous when the steps in which the barycentre and the uncertainty area references 62 and 63 are calculated dynamically.

In the example described above, steps reference 62 and 64 are used by a position calculation device 1 that comprises appropriate calculation modules (reference 72 to 74 respectively shown in FIGURE 7). For example, these calculation modules may consist of a computer program executed on a computer. Conventionally, this computer program may be stored on a memory medium (diskette, hard disk, CD-ROM, DVD, etc.) that can be read by the computer.

For example, this device 1 is integrated into a tool 4 (Fig. 1) for the management and maintenance of the cellular network that is already in the possession of the radiocommunication system operator, namely the above mentioned geographic cell radio frequency planning tool.

Step 65 - Input data to a positioning database

The position of the mobile and the uncertainty on this position resulting from the barycentre calculation according to the invention, are stored in a positioning database 2 (also called the positioning server).

For each mobile, the positioning database associates other information with this positioning and uncertainty information, for example such as:

- time dating information;
- a mobile identifier, for example such as the IMSI (International Mobile Subscriber Identity), or TMSI (Temporary Mobile Subscriber Identity);
- the nature of the measurement, namely "network capture" in this case. In the case in which the positioning database also stores positioning information obtained according to other techniques (GPS, direction finding, EOTD, etc.);
- the signalling message type (for example MIF) from which the raw positioning information was extracted (in other words the current cell identifier in this case);
- the called number;
- etc.

For example, this positioning database may be updated periodically or according to any other strategy. Optionally, it keeps information about several successive measurements of the same mobile for a relatively long period (at least an hour). For example, according to a particular application associated with these successive measurements, it would be possible to determine the direction of displacement of the mobile, or to eliminate an indetermination between two similar routes.

For example, subject to appropriate controls, it may be viewed by geodependent service providers 3_1 , 3_2 ,

who would like to obtain information that they can use to answer requests made by their customers.

It is obvious that other embodiments of the invention could be envisaged without going outside the
5 scope of this invention.

03665.00204
10220.44990